

The WTF Series

Automatic Acid Neutralizers and Filters



Benefits

- AG:** Removes particles from water as well as treats cloudy or hazy water.
- AC:** Removes objectionable color, taste and odors.
- AN:** Increases pH level of water. This helps eliminate pinhole leaks in Plumbing, blue or green stains in sinks and scratching and pitting of Porcelain and cookware.
- FE:** Helps eliminate brown stains. Requires a pH of 7.0 or greater.

Features

- 12 Day 5600 Fleck Control Valve.
- Bypass valve included.
- Fiberglass tank will not rust, durable design and efficient operation with low maintenance.
- 1" distribution tube.
- Installs directly into water line.

SPECIFICATIONS

Model	Mineral	Capacity Cu. Ft.	Service/Peak Flow Rate	Backwash Flow Rate	Tank Size Inches	Pipe Size In/Out	PH Range
WTF15AC	Carbon	1.5	6.5/8 gpm	5.0 gpm	10 x 54	3/4"	n/a
WTF25AC	Carbon	2.5	7/9 gpm	6.0 gpm	13 x 54	3/4"	n/a
WTF15ANX	Calcite MgO Mix	1.5	6.5/9 gpm	5.0 gpm	10 x 54	3/4"	5 - 6
WTF25ANX	Calcite MgO Mix	2.5	7/9 gpm	6.0 gpm	13 x 54	3/4"	5 - 6
WTF15AG	Filter Ag	1.5	5/8 gpm	5.0 gpm	10 x 54	3/4"	n/a
WTF15FE	Manganese Greensand	1.5	6.5/8 gpm	5.0 gpm	10 x 54	3/4"	n/a

Distributed by:

The WTF Series

Automatic Water Softeners



WTF Series



Benefits

- Saves on soaps and shampoos.
- Clothes will be brighter and last longer.
- Prevents scale build-up in pipes, fixtures and appliances.
- Extends the life of hot water heating.

Features

- High capacity resin.
- Fiberglass tank will not rust.
- High capacity polyethylene brine tank.
- 12 Day 5600 Fleck Control Valve.
- Bypass valve included.
- Safety float in brine tank.

SPECIFICATIONS

Model	Capacity Grains Min./Max.	Salt Lbs. Min./Max.	Service Flow Rate	Backwash Flow Rate	Pipe Size In./Out	Tank Size Inches	Brine Tank In./In./Lbs.
WTF240	18,000/24,000	6/12	8 gpm	1.5 gpm	3/4"	8 x 44	18 x 30 / 300
WTF320	24,000/32,000	8/16	10 gpm	2.0 gpm	3/4"	10 x 40	18 x 30 / 300
WTF480	36,000/48,000	12/24	12 gpm	2.4 gpm	3/4"	10 x 54	18 x 30 / 300
WTF640	48,000/64,000	16/32	15 gpm	3.5 gpm	3/4"	13 x 54	18 x 40 / 400

Distributed by:

The WTFDR Series

Automatic Demand Regeneration Water Softeners



WTFDR Series



Benefits

- Saves on soaps and shampoos.
- Clothes will be brighter and last longer.
- Prevents scale build-up in pipes, fixtures and appliances.
- Extends the life of hot water heating.
- Only regenerates when necessary.
- Salt usage can be reduced by as much as 50%.

Features

- High capacity resin.
- Fiberglass tank will not rust.
- High capacity polyethylene brine tank.
- Fleck 5600 Meter valve.
- Bypass valve included.
- Safety float in brine tank.

SPECIFICATIONS

Model	Capacity Grains Min./Max.	Salt Lbs. Min./Max.	Service Flow Rate	Backwash Flow Rate	Pipe Size In/Out	Tank Size Inches	Brine Tank In./In./Lbs.
WTF240DR	18,000/24,000	6/12	8 gpm	1.5 gpm	3/4"	8 x 44	18 x 30 / 300
WTF320DR	24,000/32,000	8/16	10 gpm	2.0 gpm	3/4"	10 x 40	18 x 30 / 300
WTF480DR	36,000/48,000	12/24	12 gpm	2.4 gpm	3/4"	10 x 54	18 x 30 / 300
WTF640DR	48,000/64,000	16/32	15 gpm	3.5 gpm	3/4"	13 x 54	18 x 40 / 400

Distributed by:

The WTF-IH Series

Iron-Handler Residential System



Benefits

- Designed to filter and remove iron while softening hard water
- Can remove up to 10 ppm of Red or Clear Iron.
- Saves on soaps and shampoos.
- Prevents scale build-up in pipes, fixtures and appliances.
- Extends the life of hot water heaters.
- Free water analysis and guaranteed equipment recommendations.

Features

- High capacity fine mesh resin.
- Fiberglass tank will not rust.
- High capacity polyethylene brine tank.
- Safety float in brine tank.
- 12 day 5600 Fleck Control Valve.
- Bypass valve included.
- Upflow brining.
- Three stage mineral bed.

SPECIFICATIONS

Model	Capacity Grains Min./Max.	Salt Lbs. Min./Max.	Service/Peak Flow Rate	Backwash Flow Rate	Pipe Size In./Out	Tank Size Inches	Brine Tank In./In./Lbs.
WTF320IH	24,000/32,000	6/12	8/15 gpm	2.0 gpm	3/4"	10 x 44	18 x 30 / 300

Distributed by: